

RP 67 TE μ P

Macchina Ripiegatrice

Macchina ripiegatrice termoincollatrice per tomaie, completa di tavolo e motore.
Sistema di erogazione colla pneumatico al fine di ottenere un funzionamento veloce ed evitare gocciolamenti.

CARATTERISTICHE TECNICHE

Velocità variabile da **0 a 2500 giri /min.**
Passo di trasporto regolabile da **0,5 a 6 mm.**
Larghezza di ripiegatura: **3,2/4/5 mm**
Lubrificazione permanente a bagno di olio
Potenza max assorbita **0,6 kW**
Alimentazione elettrica trifase **400 Volt 50/60 Hz**
Aria compressa **6 Bar**

DISPOSITIVI OPZIONALI

Guide fisse: **6 / 7 mm**
Guide regolabili: **3 - 7 mm. 5 - 10 mm.**
Motore brushless con posizionamento automatico

Dimensioni macchina cm. 110 x 55 x 130 h.
Peso macchina Kg. 137



RP 67 TE μ P

Folding Machine

Upper thermocementing and folding machine complete with table and motor. Pneumatic glue system in order to obtain fast operation and avoid dripping.

TECHNICAL DATA

Adjustable speed from **0 to 2500 rpm**
Adjustable working feed from **0,5 to 6 mm.**
Folding width: **3,2/4/5 mm.**
Permanent oil bath lubrication positioning
Absorbed power max. **0,6 kW**
Power supply three-phase **400 Volt 50/60 Hz**
Compressed air **6 Bar**

OPTIONALS

Fixed guides: **6 / 7 mm.**
Adjustable guides: **3 - 7 mm 5 - 10 mm.**
Brushless motor with automatic positioning

Machine dimensions cm. 110 x 55 x 130 h.
Machine weight Kg. 137



RBT
French Binding



Roll Top



Ripiegatura
Folding

Le caratteristiche tecniche sono indicative e non vincolanti.
Technical Data are indicative and not binding



SAGITTA

Officina Meccanica srl
Corso Novara 163
27029 Vigevano (PV)
Italy

Phone +39 0381 75701 / +39 0381 75702

info@sagitta.it
www.sagitta.it